


VARSAVIA

Scheda tecnica / Technical specifications / Fiche technique rev.00 04/03/14




- 1 Interruttore e presa di alimentazione / Switch and power socket / Interrupteur et prise d'alimentation
 2 Ingresso aria / Combustion air inlet / Entrée de l'air de combustion
 3 Uscita fumi / Fumes outlet / Sortie des fumées

Potenza introdotta max/min / Introduced power max/min / Puissance introduit max/min:	28 kW / 9.55 kW
Potenza resa all'acqua max/min / H2O power max/min / Puissance H2O max/min:	21 kW / 5.70 kW
Potenza resa per convezione e irraggiamento max/min / Convectional and irradiated power max/min / Puissance pour convection et rayonnement en ambiance max/min:	3.60 kW / 1.38 kW
Rendimento a potenza max/min / Efficiency at max/min power / Rendement puissance max/min :	87,8 % / 88,2%
Volume riscaldabile min/max / Heating capacity min/max / Volume chauffable min/max:	250-700 m ³
Consumo orario max/min / Pellet consumption max/min / Consommation horaire max/min:	5.6 kg/h / 1.6 kg/h
Autonomia min/max / Autonomy min/max / Autonomie min/max:	6.2 h / 21.8 h
Alimentazione elettrica / Power supply / Alimentation électrique:	230 V 50 Hz
Assorbimento elettrico nominale / Nominal power absorption / Absorption électrique nominale:	200 W
Capienza caldaia / Boiler capacity / Contenu d'eau thermo-poele:	18,4 L
Capienza serbatoio / Pellet tank capacity / Capacité du reservoir:	35 Kg
Combustibile / Fuel / Combustible:	Pellet Ø6mm
Diametro uscita fumi / Fumes outlet diameter / Diamètre sortie de fumées:	Ø 100 mm
Pressione di esercizio massima / Maximum operating pressure / Pression d'exercice max. :	1,5 bar
Tiraggio minimo / Required draught / Exigences pour tirage de la cheminée:	10 Pa
Temperatura fumi a potenza max/min / Combustion fumes temperature at max/min power / Température de sortie des gaz puissance max/min:	242,8 °C / 124,56 °C


Allacciamento senza kit
 Connection without kit
 Branchement sans kit

- 1-Mandata H2O termosifoni ¾" / H2O radiators lock ¾" / Raccord départ chauffage ¾"
 2-Tubo scarico H2O valvola sicurezza / Safety valve H2O outlet / Tuyau évacuation valvule de sécurité ½"
 3-Ritorno H2O termosifoni ¾" / H2O radiators return ¾" / Raccord retour chauffage ¾"
 4-Entrata H2O linea idrica ½" / H2O waterworks intake ½" / Raccord de remplissage ½"



Allacciamento con kit
Connection with kit
Branchement avec kit

- 1-Mandata H2O termosifoni 3/4" / H2O radiators lock 3/4" / Raccord départ chauffage 3/4"
- 2-Uscita sanitari calda 1/2" / Hot H2O output 1/2" / Sortie d'eau chaude 1/2"
- 3-Entrata H2O linea idrica 1/2" / H2O waterworks intake 1/2" / Raccord de remplissage 1/2"
- 4-Rubinetto carico / Water intake tap / Robinet de remplissage
- 5-Ritorno H2O termosifoni 3/4" / H2O radiators return 3/4" / Raccord retour chauffage 3/4"
- 6-Tubo scarico H2O valvola sicurezza 1/2" / Safety valve H2O outlet / Tuyau évacuation valvule de securité 1/2"



- Display controllo digitale / Digital control display / Affichage controle digital
- Programma settimanale / Weekly program / Programme hebdomadaire
- Termostato ambiente / Room thermostat / Thermostat d'ambiance
- Funzionamento manuale-automatico / Manual – automatic functioning / Fonctionnement manuel-automatique
- Piedini regolabili / Adjustable feet / Pieds réglables